SIEMENS

Data sheet 6AV2143-8GB50-0AA0



spare part SIMATIC HMI, IWP700, industrial web panel, key/touch operation, 7" TFT display, 65536 colors, PROFINET interface, HTML5, stand-alone, no WinCC configuration required, contains open source software, which is provided free of charge

General information	
Product type designation	IWP700
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	7 in
Display width	154.1 mm
Display height	85.9 mm
Number of colors	65 536
Resolution (pixels)	
● Horizontal image resolution	800 pixel
● Vertical image resolution	480 pixel
Backlighting	
● MTBF backlighting (at 25 °C)	20 000 h
● Backlight dimmable	Yes
Control elements	
Keyboard	
● Function keys	
— Number of function keys	8
— Number of function keys with LEDs	0
● Keys with LED	No
● System keys	No
● Numeric keyboard	Yes; Onscreen keyboard
● alphanumeric keyboard	Yes; Onscreen keyboard
Touch operation	
● Design as touch screen	Yes; Analog-resistive
● Design as multi-touch screen	No
● Monitor keyboard	Yes
Installation type/mounting	
Mounting type	Mounting clips
Mounting position	vertical
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
maximum permissible angle of inclination without external ventilation	35°
RFID reader can be installed	No
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V

© Copyright Hmitop

permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	230 mA
Starting current inrush I²t	0.2 A²·s
Power	
Active power input, typ.	5.5 W
Processor	
Processor type	ARM
Storage	
Type of memory	DDR3-SDRAM
Flash	Yes
RAM	Yes
Memory available for user data	10 Mbyte
Type of output	
Acoustics	
● Buzzer	Yes
● Speaker	No
Time of day	
Clock	
● Hardware clock (real-time)	Yes
● Software clock	Yes
● retentive	Yes; Back-up duration typically 6 weeks
● synchronizable	Yes
Interfaces	
Number of industrial Ethernet interfaces	1
Number of RS 485 interfaces	0
Number of RS 422 interfaces	0
Number of RS 232 interfaces	0
Number of USB interfaces	1; Up to 16 GB
Number of 20 mA interfaces (TTY)	0
Number of parallel interfaces	0
Number of other interfaces	0
Number of SD card slots	0
With software interfaces	No
Industrial Ethernet	
● Industrial Ethernet status LED	2
Protocols	
PROFINET	No
Supports protocol for PROFINET IO	No
IRT	No
PROFIBUS	No
EtherNet/IP	No
MPI	No
Protocols (Ethernet)	
● TCP/IP	Yes
● DHCP	Yes
● SNMP	Yes
● DCP	Yes
● LLDP	Yes
WEB characteristics	
● HTTP	Yes
● HTTPS	Yes
● HTML	Yes
● XML	Yes
● CSS	Yes
● JavaScript	Yes
Redundancy mode	
Media redundancy	

© Copyright Hmitop

— MRP	No
Further protocols	
● MODBUS	No
EMC	
Emission of radio interference acc. to EN 55 011	
● Limit class A, for use in industrial areas	Yes
● Limit class B, for use in residential areas	No
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	
● Enclosure Type 4 at the front	Yes
● Enclosure Type 4x at the front	Yes
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
Use in hazardous areas	
● ATEX Zone 2	No
● ATEX Zone 22	No
● IECEx Zone 2	No
● IECEx Zone 22	No
● cULus Class I Zone 1	No
● cULus Class I Zone 2, Division 2	No
● FM Class I Division 2	No
Marine approval	
● Germanischer Lloyd (GL)	No
● American Bureau of Shipping (ABS)	No
● Bureau Veritas (BV)	No
● Det Norske Veritas (DNV)	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (Class NK)	No
● Polski Rejestr Statkow (PRS)	No
● Chinese Classification Society (CCS)	No
Ambient conditions	
Ambient temperature during operation	
Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	50 °C
Operation (max. tilt angle)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, max.	40 °C
Operation (vertical installation, portrait format)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	40 °C
Operation (max. tilt angle, portrait format)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, max.	35 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Relative humidity	
● Operation, max.	90 %; no condensation
Operating systems	
proprietary	Yes
pre-installed operating system	
● Windows CE	No
Software	
Web browser	Yes

© Copyright Hmitop

Languages	
Online languages	
● Number of online/runtime languages	2
Peripherals/Options	
Printer	No
SIMATIC HMI MM memory card: Multi Media Card	No
SIMATIC HMI SD memory card: Secure Digital memory card	No
SIMATIC HMI CF memory card Compact Flash Card	No
USB memory	Yes
SIMATIC IPC USB Flashdrive (USB stick)	Yes
SIMATIC HMI USB stick	Yes
Mechanics/material	
Enclosure material (front)	
● Plastic	Yes
● Aluminum	No
● Stainless steel	No
Dimensions	
Width of the housing front	214 mm
Height of housing front	158 mm
Mounting cutout, width	197 mm
Mounting cutout, height	141 mm
mounting depth	39 mm
Weights	
Weight (without packaging)	780 g
Weight (with packaging)	990 g

Classifications

	Version	Classification
eClass	16	27-33-02-01
eClass	14	27-33-02-01
eClass	12	27-33-02-01
eClass	9.1	27-33-02-01
eClass	9	27-33-02-01
eClass	8	27-24-23-02
eClass	7.1	27-24-23-02
eClass	6	27-24-23-02
ETIM	10	EC001412
ETIM	9	EC001412
ETIM	8	EC001412
ETIM	7	EC001412
IDEA	4	6607
UNSPSC	15	43-21-15-06

Approvals / Certificates

General Product Approval

Manufacturer Declaration

China RoHS

General Product Approval	EMV

© Copyright Hmitop

last modified: 3/12/2024

Subject to change without notice
© Copyright Hmitop